



System Tested and Certified by NSF International against NSF/ANSI Standard 177 for the reduction of free available Chlorine.



PERFORMANCE DATA SHEET | SF-7C

NSF/ANSI STANDARD 177

This System has been tested according to NSF/ANSI Standard 177 for the reduction of free available chlorine. The concentration of free available chlorine in water entering the System was reduced to a concentration less than or equal to the permissible limit for water leaving the System, as specified by NSF/ANSI Standard 177. The System has not been evaluated for free

available chlorine reduction performance in the presence of chloramines. Free available chlorine reduction performance may be impacted by the presence of chloramines in the water supply. Please contact your local water utility to determine if chloramines are used in treating your water.

SHOWER FILTER SYSTEM SPECIFICATIONS [Model: SF-7C]

Installation Shower
 EPA Establishment Number 63018-NV-001
 Rated Capacity 7,000 gallons (37,854 L)
 Replacement Cartridge RCSF-7
 Rated Service Flow @ 80 psi 2.5 gal/min (9.46 L/min)
 Housing Construction High Impact, Plated ABS

Maximum Working Pressure 100 psig (689.5 kPa)
 Minimum Working Pressure 30 psig (206.8 kPa)
 Maximum Operating Temperature 140° F (60° C)
 Minimum Operating Temperature 34° F (1° C)

U.S. Patent Number: 5,545,314

1. Minimum chlorine reduction per NSF/ANSI 177, $\geq 50\%$ free available chlorine (FAC) when used with an influent challenge water of 2 mg/L FAC. Average chlorine reduction per NSF/ANSI 177, 73.5%.
2. For this System to continue to perform as tested and represented, use only genuine, NSF certified, WaterChef Replacement Cartridges (RCSF-7).
3. The actual capacity of your Cartridge may vary from the rated capacity. This may be due to the volume of contaminants actually present in your water supply. Replace the Cartridge upon the first occurrence:
 - Every three to four months
 - The flow rate diminishes
 - When you notice an odor reoccurrence
 - When the rated capacity of the cartridge has been reached
4. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the System.
5. Installation of this product must comply with all state and local laws and regulations. Refer to your local agencies for details.

6. The contaminants or other substances removed or reduced by this System are not necessarily in all users' water.
7. The approximate cost for a pack of two (2) Shower Filter Replacement Cartridges is \$60.00 or less.
8. For limited warranty and installation and operating instructions, please refer to the Installation, Use & Care Guide.
9. For more information regarding the purchase of genuine, NSF certified, WaterChef Replacement Cartridges and replacement parts, contact:

WaterChef Customer Care
 3760 Barron Way
 Reno, NV 89511
 tel: 1.800.879.8909
 email: info@waterchef.com

